

BINOPTIC electronic tap

Ref. 379DER

Mains supply







DESCRIPTION

BINOPTIC electronic tap - Ref. 379DER



Electronic basin tap for cross wall installation.
 Independent IP65 electronic control unit.
 230/12V mains supply with transformer.
 Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Active, infrared presence detection, sensor at the end of the spout optimises detection.
 Filters and solenoid valves M3/8".
 Chrome-plated brass body.
 Chrome-plated spout L.205mm for cross wall installation ≤ 190mm.
 Cable for sensor L. 120mm, flexibles and mounting all pass through the same hole.
 Anti-blocking safety.
 Spout with smooth interior and low volume of water (reduces niches where bacteria can develop).
 10-year warranty.

ADVANTAGES

-  Independent IP65 electronic control unit
-  Water savings up to 90%
-  Total hygiene: no manual contact
-  Anti-bacterial proliferation duty flush

TECHNICAL FEATURES

BINOPTIC electronic tap - Ref. 379DER

Connector	M3/8"
Technology	Electronic
Spout length	205mm
Flow rate	3 lpm
Standards and certifications	     
Warranty	

