



NB! Fornire separatamente:

- N° 2 Dadi M4
- N° 2 Viti M4x16 T.E.
- N° 2 Ranelle dentellate ø 4

Targhetta Dati

ET.: A1 MOD.: 274



EFCR12Y0.A5
230 V~ 50/60 Hz 0,37 A
53-12 W 1300/1500 min⁻¹



INZAGO (MI) THERM.PROT. CL. B
MADE IN ITALY 00X00 / 01
FAX:02.9549825

2	17/02/10	RIFATTO LUCIDO	<i>E.P.</i>				
ED.	DATA DATE	MODIFICHE MODIFICATIONS	DIS. DRWN	ED.	DATA DATE	MODIFICHE MODIFICATIONS	DIS. DRWN
DENOMINAZIONE / DESCRIPTION				TOLLERANZE GENERALI / GENERAL TOLERANCE			
MOTORE Chiuso 85x85 - 4Poli schermati				DIS. DRWN <i>E.P.</i>			
P.20 12Wr. 230V~ 50/60Hz				SCALA SCALE <i>///</i>			
				DATA DATE 04/08/1999			
NOME FILE / FILE NAME			DISEGNO NR. / DRAWING NO.		EDIZIONE		
EFCR10A-TC2 / EFCR10A-UTC2			EFCR12Y0.A5		2		
SOSTITUITO DA / REPLACED BY			SOSTITUISCE / REPLACES		DIS. CLIENTE / CUST. DRW.		REF. CATALOGO / CATALOG REF.
MA-VIB S.p.A. Inzago (MI) Italy www.mavib.com							